PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS



STRUCTURAL SPECIFICATIONS

DESIGN BASED ON AWC 110 MPH EXPOSURE B WFCM
(PREPARED IN ACCORDANCE WITH 780 CMR 5301.2.1.1)

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GUAY
STRUCTURAL
No. 43126
REGISTERED
PROFESSIONAL ENGINEER

IMPORTANT NOTE

THE ASSEMBLY OF THE STRUCTURE SHALL FOLLOW THESE SPECIFICATIONS, THE REFERENCE CODES AND THE BUILDING PLANS IN ITS ENTIRETY IN ORDER TO COMPLY WITH THE REQUIREMENTS OF 780 CMR 5301.2.1.1 ITEM 1

TRI - AN
DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
COVER

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-1

PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS



STRUCTURAL SPECIFICATIONS

DESIGN BASED ON AWC 110 MPH EXPOSURE B WFCM GUIDE
(PREPARED IN ACCORDANCE WITH 780 CMR 5301.2.1.1)

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GUAY
STRUCTURAL
No. 47126
REGISTERED
PROFESSIONAL ENGINEER

IMPORTANT NOTE

THE ASSEMBLY OF THE STRUCTURE SHALL FOLLOW THESE SPECIFICATIONS, THE REFERENCE CODES AND THE BUILDING PLANS IN ITS ENTIRETY IN ORDER TO COMPLY WITH THE REQUIREMENTS OF 780 CMR 5301.2.1.1 ITEM 1

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
COVER

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-1

'ES

)RAWINGS ARE TO BE USED WITH THE ENTIRELY OF DRAWINGS.
:GULATIONS ARE TO BE STRICTLY FOLLOWED. METHODS OF
N AND ERECTION OF STRUCTURAL MEMBERS IS THE
S RESPONSIBILITY.
TOR IS RESPONSIBLE FOR DISSEMINATION OF ALL REVISIONS
MENTS TO THE SUB-CONTRACTORS.
:ARE HAS BEEN TAKEN IN THE PREPARATION OF ALL DRAWINGS
ATIONS. HOWEVER, THE DESIGNER/CONSULTANT DOES NOT
GAINST HUMAN ERROR AND FOR THAT REASON IT IS
IAT THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AND
UST VERIFY ALL CONDITIONS AND DIMENSIONS OF THE
DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF
/CONSULTANT BEFORE PROCEEDING.
LL BE IN COMPLIANCE WITH NATIONAL, STATE AND LOCAL

RK AND MATERIALS SHALL BE COORDINATED WITH OWNER AND
THE OWNER, BUILDER AND CONTRACTORS SHALL CHECK AND
IENSIONS BEFORE STARTING WORK.
SHALL BE AS SELECTED BY OWNER. CONTRACTOR TO
/ITH OWNER.

BER

MAY NOT APPLY TO THIS PROJECT)
LUMBER SHALL BE KILN DRIED 19% MAXIMUM MOISTURE
MBER SHALL MEET AS A MINIMUM THE FOLLOWING DESIGN
SPRUCE-PINE-FIR":
CONSTRUCTION GRADE Fb=800 , Fv=70 , Fc=750
S/RAFTERS NO. 1 GRADE Fb=1150 , Fv=70
1 GRADE Fb= 800 , Fv=65 , Fc=675
IG OF FRAMING, PLATES, SILLS, SHEATHING AND OTHER WOOD
ALL BE IN ACCORDANCE WITH THE DETAILS SHOWN AND
UIREMENTS OF THE MASSACHUSETTS STATE BUILDING CODE.
S SHOWN ARE A MANUFACTURED BY SIMPSON STRONG-TIE CO.
JTIONS MUST BE APPROVED IN WRITING BY AN ENGINEER.
OF ALL CONNECTORS SHALL BE IN STRICT ACCORDANCE
NUFACTURER'S INSTRUCTIONS AND MUST EMPLOY ALL
STENERS.
'ORS SHALL BE HOT DIP GALVANIZED.
ONNECTOR FASTENERS BEFORE LOADING THE JOINT.
S NOT ACCEPTABLE FOR ANY CONNECTIONS.
FRAMING MEMBERS SHALL BE TREATED PER AWPA C2/C9/ CCA
BERS IN CONTACT WITH SOIL SHALL BE TREATED PER AWPA
.60. JOB SITE FABRICATION CUTS AND BORES SHALL BE
CCORDANCE WITH AWPA STD M4.
TURED LVL WOOD FRAMING COMPONENTS SHALL HAVE THE
HYSICAL PROPERTIES AS A MINIMUM:
b=2900, Fv=240
AMING SHALL BE 2" x 10" PRESSURE TREATED @ 16" O.C. OR

:RWISE NOTED)

WORK AND MATERIALS SHALL COMPLY WITH THE
IS FOR STRUCTURAL CONCRETE FOR BUILDINGS (ACI 301-89).
SHALL HAVE A 28-DAY COMPRESSIVE STRENGTH OF 3000 PSI
MUM 1-INCH AGGREGATE AND MAXIMUM 6% AIR ENTRAPMENT
CONCRETE EXPOSED TO MOISTURE.
NG STEEL SHALL BE DEFORMED BARS OF NEW BILLET STEEL
TO ASTM A 615 GRADE 60.
VER OF REINFORCING BARS SHALL BE AL FOLLOWS:
NCRETE PLACED DIRECTLY AGAINST EARTH.
HER LOCATIONS.
L CONSTRUCTION JOINTS ARE ALLOWED, UNLESS
SHOWN ON THE DRAWINGS OR ALLOWED IN WRITING BY AN

R BASE PLATES SHALL BE NON-SHRINK AND NON-METALLIC,
M COMPRESSIVE STRENGTH OF 5000 PSI.
FOUNDATION SHALL BE ADEQUATELY TIED TOGETHER AND
RM TRUE LINES, SQUARE CORNERS AND PLUMB WALLS.
SHALL BE POURED CONTINUOUSLY WITH NO JOINTS. DO NOT
E THAT BECOMES NON-PLASTIC AND UNWORKABLE.
RETE FOOTINGS SHALL BE POURED ON UNDISTURBED SOIL.

SIMPSON STRONG-TIE NOTES

1. Outdoor environments are generally more corrosive to steel. If you choose to use ZMAX® or HDG finish or stainless steel material on an outdoor project, you should periodically inspect your connectors and fasteners or have a professional inspection performed. Regular maintenance, including water-proofing of the wood used in your outdoor project is also a good practice.
2. Coatings Available:
   - 2.1. ZMAX: Galvanized (G185) 1.85 oz. of zinc per square foot of surface area. (hot-dip galvanized per ASTM A653 total both sides). These products require hot-dip galvanized fasteners (fasteners which meet the specifications of ASTM A153).
   - 2.2. HDG - Hot Dip Galvanized: Products are hot-dip galvanized after fabrication (14 ga. and thicker). The coating weight increases with material thickness. The minimum specified coating weight is 2.0 oz. per square foot. (per ASTM A123 total both sides). These products require hot-dip galvanized fasteners (fasteners which meet the specifications of ASTM A153).
   - 2.3. SS - Stainless Steel: Connectors are manufactured from Type 316L stainless steel, and provide greater durability against corrosion. Stainless-steel nails are required with stainless-steel products, and are available from Simpson Strong-Tie.
3. When using stainless steel connectors, use stainless steel fasteners. When applications allow the use of ZMAX/HDG galvanized connectors, use HDG fasteners that meet the specifications of ASTM A153 or equivalent coating offered on Simpson Strong-Tie fasteners.
4. Due to many variables involved with outdoor construction, Simpson Strong-Tie cannot provide estimates on service life of connectors, anchors or fasteners.
5. To obtain optimal performance from Simpson Strong-Tie products, the products must be installed properly and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.
6. All installation notes and guidelines within the current *Wood Construction Connectors* catalog shall apply for the connectors, anchors, and fasteners shown.
7. Simpson Strong-Tie reserves the right to change the specifications, design and models shown without notice or liability for such changes.
8. Simpson Strong-Tie does not guarantee the performance or safety of products that are modified, improperly installed or not used in accordance with the design.
9. All references to bolts or machine bolts (MB) are structural quality through bolts (*not lag screws or carriage bolts*) equal to or better than ASTM A307, grade A. Bolt holes shall be at least a minimum 1/32" and no more than a maximum of 1/16" larger than the bolt diameter per 2005 NDS Section 11.1.2.
10. Unless noted otherwise, all references to standard cut washers refer to Type A plain washers (W) conforming to the dimensions shown in ASME B18.22.1 for the appropriate rod sizes.
11. Unless stated otherwise, Simpson Strong-Tie cannot and does not make any representation regarding the suitability of use or load-carrying capacities of connectors installed with improper fasteners.

SIMPSON STRONG-TIE FASTENER NOTES



Fastener Notes:
1. The specified quantity, type and size of fastener must be installed in the correct holes on the connector to achieve published loads. Incorrect fastener selection or installation can compromise connector performance and could lead to failure.
2. Nail diameter assumes no coating. See technical bulletin *T-NAILGUIDE* for more information.
3. The Simpson Strong-Drive® SD structural-connector screw is the only screw approved for use with our connectors.
4. NAIL reference in tables: 16d = 16d common, 10d = 10d common



Fastening Identification

STRUCTURAL SPECIFICATIONS

DESIGN BASED ON AWC 110 MPH EXPOSURE B WFCM GUIDE
(PREPARED IN ACCORDANCE WITH 780 CMR 5301.2.1.1)

IMPORTANT NOTE

THE ASSEMBLY OF THE STRUCTURE SHALL FOLLOW THESE SPECIFICATIONS, THE REFERENCE CODES AND THE BUILDING PLANS IN ITS ENTIRETY IN ORDER TO COMPLY WITH THE REQUIREMENTS OF 780 CMR 5301.2.1.1 ITEM 1

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
NOTES

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-2



LEFT SIDE ELEVATION PLAN
SCALE : 1/4" = 1'-0"



RIGHT SIDE ELEVATION PLAN
SCALE : 1/4" = 1'-0"



FRONT ELEVATION PLAN
SCALE : 1/4" = 1'-0"

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. RIVAY
STRUCTURAL
No. 43126
REGISTERED PROFESSIONAL ENGINEER

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
ELEVATION PLAN

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-3



DECK FLOOR PLAN

SCALE : 3/16" = 1'-0"

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GRAY
STRUCTURAL
No. 43126
REGISTERED
PROFESSIONAL ENGINEER

TRI - AN
DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
DECK
FLOOR
PLAN

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-4



DECK FOOTING PLAN

SCALE : 3/16" = 1'-0"

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
DECK FOOTING PLAN

DRAWN BY: T.DASILVA

DATE: 12/24/15 REV#1

SCALE: AS SHOWN

JOB NO.: 2015-09-A

SHEET NO:
A-5

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GUAY
STRUCTURAL
No. 42126
REGISTERED
PROFESSIONAL ENGINEER

SPECIAL NOTE:
FLOOD ELEVATION IS AE EL. 13





COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GRAY
STRUCTURAL
No. 42126
REGISTERED
PROFESSIONAL ENGINEER

DECK SECTIONAL VIEW (D1)

SCALE : 3/8" = 1'-0"

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
DECK SECTION VIEW (D1)

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO.
A-6



	Size (in.)	Model No.	Thread Length (in.)
▷	¼" x 3½"	SDS25312	2¼
	¼" x 5"	SDS25500	2¾

1. ▷ indicates connector is available in stainless steel. Add SS to model number when ordering.
2. Refer to current *F-SDSLDGR* for spacing and additional information.
3. The screws shall be staggered from the top to the bottom along the horizontal run of the deck ledger per IRC 2009 Section R502.2.2.1.1.

Installation:
- Install Simpson Strong-Tie SDS wood screws with a ⅜" hex head driver.
- SDS screws install best with a low speed ½" drill.

LEDGERBOARD CONNECTION
SCALE : NONE



Installation:
- ABA, ABU - for pre-pour installed anchors. For Simpson Strong-Tie epoxy or mechanical anchors, select and install in accordance with www.strongtie.com.
- Products require washers between the nut and the base. Washers are supplied with the ABU but not the ABA, which requires a standard cut washer.

Model No.	Post Size	Dimensions (in.) W	L	H	HB	Anchor Dia.	Post Fasteners Nails	SD Screws	Machine Bolts Qty.	Dia.
ABA44Z	4x4	3 9/16	3 1/8	3 1/16	-	1/2	6-10d	6-SD #9x1½	-	-
ABU44Z	4x4	3 9/16	3	5 1/2	1 3/4	5/8	12-16d	12-SD #10x1½	2	1/2
ABA46Z	4x6	3 9/16	5 3/16	3 1/8	-	5/8	8-16d	8-SD #10x1½	-	-
ABU46Z	4x6	3 9/16	5	7	2 5/8	5/8	12-16d	-	2	1/2
ABA66Z	6x6	5 1/2	5 1/4	3 1/8	-	5/8	8-16d	8-SD #10x1½	-	-
ABU66Z	6x6	5 1/2	5	6 1/16	1 3/4	5/8	12-16d	-	2	1/2
ABU88Z	8x8	7 1/2	7	7	-	2 - 5/8	18-16d	-	-	-

1. ▷ indicates connector is available in stainless steel. Replace Z in model number with *SS* when ordering.
2. Refer to current *Wood Construction Connectors* catalog for additional information.

6x6 POST / BEAM CONNECTION
SCALE : NONE



Typical LUS28Z Installation

Installation:
- LUS hangers install with double shear nailing.
- For installations into single 2x headers or ledgers, use the specified full length fasteners into the joist and the following fasteners into the header for reduced loads in accordance with www.strongtie.com:
  - 10dx1½ nails for installations with Nails
  - SD #9x1½ for LUS28Z and LUS210Z installations with SD Screws
  - SD #10x1½ for LUS26-2Z and LUS210-2Z installations with SD Screws

Dimensions (in.) W	H	B	Fasteners Nails Header	Joist	SD Screws Header	Joist
1 9/16	4 3/4	1 3/4	4-10d	4-10d	-	-
1 9/16	6 5/8	1 3/4	6-10d	4-10d	6-SD #9x2½	4-SD #9x2½
1 9/16	7 13/16	1 3/4	8-10d	4-10d	8-SD #9x2½	4-SD #9x2½
3 1/8	4 7/8	2	4-16d	4-16d	4-SD #10x2½	4-SD #10x2½
3 1/8	9	2	8-16d	6-16d	8-SD #10x2½	6-SD #10x2½

connector is available in stainless steel. Replace Z in model number
rdering.
nt *Wood Construction Connectors* catalog for additional information.



Installation:
- For HUC installations, models have triangle and round holes. To achieve maximum loads, fill both round and triangle holes (fastener quantities listed fill both holes).
- For installations into single 2x headers or ledgers, use the specified full length fasteners into the joist and the following fasteners into the header for reduced loads in accordance with www.strongtie.com:
  - 10dx1½ nails for installations with Nails
  - SD #9x1½ for LUC26Z and LUC210Z installations with SD Screws

Model No.	Dimensions (in.) W	H	B	Fasteners Nails Header	Joist	SD Screws Header	Joist
▷ LUC26Z	1 9/16	4 3/4	1 3/4	6-10d	4-10dx1½	6-SD #9x2½	4-SD #9x1½
▷ LUC210Z	1 9/16	7 3/4	1 3/4	10-10d	6-10dx1½	10-SD #9x2½	6-SD #9x1½
HUC26-2Z	3 1/8	5 3/8	2 1/2	12-16d	6-10d	-	-
▷ HUC28-2Z	3 1/8	7	2 1/2	14-16d	6-10d	-	-
▷ HUC210-2Z	3 1/8	8 13/16	2 1/2	18-16d	10-10d	-	-

1. ▷ Indicates connector is available in stainless steel. Replace Z in model number with *SS* when ordering.
2. Refer to current *Wood Construction Connectors* catalog for additional information.

JOIST HANGER DETAIL
SCALE : NONE



Installation:
- Use all specified fasteners.

Model No.	Fasteners Nails To Joist	To Beam	SD Screws To Joist	To Beam
H1Z	6-8dx1½	4-8dx1½	6-SD #9x1½	4-SD #9x1½
H2.5Z	5-8dx1½	5-8dx1½	5-SD #9x1½	5-SD #9x1½
H8Z	5-10dx1½	5-10dx1½	5-SD #9x1½	5-SD #9x1½

1. indicates connector is available in stainless steel. Replace Z in model number with *SS* when ordering.
2. Refer to current *Wood Construction Connectors* catalog for additional information.

HURRICANE CONNECTOR DETAIL
SCALE : NONE

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. DUNN
STRUCTURAL
No. 43126
REGISTERED
PROFESSIONAL ENGINEER

TRI - AN DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
DECK FRAMING DETAILS

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-8



PICTORIAL VIEW
SCALE : NONE



PICTORIAL VIEW
SCALE : NONE

TRI - AN
DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
PICTORIAL VIEWS

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GUAY
STRUCTURAL
No. 43126
REGISTERED
PROFESSIONAL ENGINEER

SHEET NO:
A-9



DECK FRAMING PLAN

SCALE : 3/16" = 1'-0"

COMMONWEALTH OF MASSACHUSETTS
ROBERT A. GLIAY
STRUCTURAL
No. 43128
REGISTERED
PROFESSIONAL ENGINEER

TRI - AN
DESIGN & CONSTRUCTION SERVICES

NO.	DESCRIPTION	DATE
0	PRELIMINARY	12/14/15
1	PERMIT SET	12/24/15

PROJECT NAME:
PROPOSED NEW DECK STRUCTURE
FOR
MR. JOSE MATOS
103 WILLARD STREET
NEW BEDFORD, MASSACHUSETTS

SHEET NAME:
DECK FRAMING PLAN

DRAWN BY: T.DASILVA
DATE: 12/24/15 REV#1
SCALE: AS SHOWN
JOB NO.: 2015-09-A

SHEET NO:
A-7